

# DATASHEET

## FUJITSU CELSIUS W380

### WORKSTATIONS

WELCOME TO A WORLD OF POWER

The CELSIUS W380 is the versatile all-round workstation for entry-level graphics applications. Powered by the latest Intel® processors, it is the ideal choice business environments such as entry-level CAD, digital content creation and finance. Thanks to the ISV certification process you can be guaranteed that your preferred professional applications will run with maximum speed and system stability.

#### GOOD PERFORMANCE

Higher productivity

- State-of-the art processors, graphic cards and hard disk drives

#### ERGONOMICS

Quiet system for a pleasant working environment

- Optimized thermal management, low-noise chassis and silent fans

#### FLEXIBILITY

Suitable for all application areas

- Excellent flexibility for all tasks

#### LEADING WORKSTATION APPLICATION CERTIFICATION



Maximum compatibility and performance with customer-preferred applications

- Full support for ISV applications and easy integration into existing IT environments

#### BUILT TO ORDER

Free configurability for all product lines

- Customer is given a system optimized for his requirements



# COMPONENTS

## PROCESSOR

Intel® Core™ i5 processor i5-670 (2C/4T, 3.46 GHz, 4 MB, Intel® HD Graphics)  
 Intel® Core™ i5 processor i5-660 (2C/4T, 3.33 GHz, 4 MB, Intel® HD Graphics)  
 Intel® Core™ i5 processor i5-650 (2C/4T, 3.20 GHz, 4 MB, Intel® HD Graphics)  
 Intel® Core™ i3 processor i3-530 (2C/4T, 2.93 GHz, 4 MB, Intel® HD Graphics)  
 Intel® Xeon® processor X3450 (4C/8T, 2.66 GHz, 8 MB)  
 Intel® Pentium® processor G6950 (2C/2T, 2.80 GHz, 3 MB, Intel® HD Graphics)

## MEMORY MODULES

4 GB (1 module(s) 4 GB) DDR3, unbuffered, non-ECC, 1333 MHz, PC3-10600, DIMM  
 4 GB (1 module(s) 4 GB) DDR3, unbuffered, ECC, 1333 MHz, PC3-10600, DIMM  
 2 GB (1 module(s) 2 GB) DDR3, unbuffered, non-ECC, 1333 MHz, PC3-10600, DIMM  
 2 GB (1 module(s) 2 GB) DDR3, unbuffered, ECC, 1333 MHz, PC3-10600, DIMM

## GRAPHICS ADD ON CARDS (OPTIONAL)

Midrange 3D: NVIDIA® Quadro FX 1800, 768 MB, PCIe x16, DL-DVI-I, 2x DP  
 Midrange 3D: NVIDIA® Quadro FX 580, 512 MB, PCIe x16, DL-DVI-I, 2x DP  
 Entry 3D: NVIDIA® Quadro FX 380, 256 MB, PCIe x16, 2x DL-DVI-I  
 Entry 3D: ATI FirePro™ V3700, 256 MB, PCIe x16, 2x DL-DVI-I  
 Multi monitor 2D: NVIDIA® Quadro NVS 450, 512 MB, PCIe x1, 4 x DP  
 Professional 2D: NVIDIA® Quadro NVS 290, 256 MB, PCIe x16, 2x SL DVI-I

## HARD DISK DRIVES (INTERNAL)

SSD SATA, 256 GB, 2.5-inch  
 SSD SATA, 128 GB, 2.5-inch  
 SATA II, 10000 rpm, 300 GB, 2.5-inch, S.M.A.R.T.  
 SATA II, 7200 rpm, 1000 GB, 3.5-inch, S.M.A.R.T. business critical  
 SATA II, 7200 rpm, 1000 GB, 3.5-inch, S.M.A.R.T.  
 SATA II, 7200 rpm, 750 GB, 3.5-inch, S.M.A.R.T. business critical  
 SATA II, 7200 rpm, 500 GB, 3.5-inch, S.M.A.R.T.  
 SATA II, 7200 rpm, 320 GB, 3.5-inch, S.M.A.R.T.  
 SATA II, 7200 rpm, 250 GB, 3.5-inch, S.M.A.R.T.  
 SATA II, 7200 rpm, 160 GB, 2.5-inch, S.M.A.R.T.

## Hard disk notes

One Gigabyte equals one billion bytes, when referring to hard disk drive capacity.  
 2.5-inch drives will be mounted in the 3.5-inch bays

## DRIVES (OPTIONAL)

Blu-ray Disc Triple Writer  
 DVD-ROM  
 DVD Super Multi  
 MultiCard Reader 20in1, 3,5-Inch

## INTERFACE ADD ON CARDS/COMPONENTS (OPTIONAL)

WLAN III, 802.11g/Draft-n (Windows only)  
 Parallel Interface  
 Gigabit Ethernet PCIe x1  
 eSATA Interface  
 Dual serial card, PCI, EX-43092

## Base unit

CELSIUS W380

## MAINBOARD

### Mainboard type

D2917

### Formfactor

BTX

### Chipset

Intel® 3450

### Processor socket

LGA 1156

### Processor quantity maximum

1

### Memory slots

4 DIMM (DDR3) ECC/non-ECC

### Supported capacity RAM (max.)

16 GB

<b>MAINBOARD</b>	
<b>Memory frequency</b>	1333 MHz
<b>Memory notes</b>	In configurations with 4 GB and more the visible memory may be reduced to approximately 3.5 GB or less (for 32-bit operating systems) and configurations with 8 GB the visible memory may be reduced to approximately 7.5 GB or less (depending on system configuration).
<b>LAN</b>	Built-in 10/100/1000 MBit/s Intel® 82578 LM
<b>WLAN</b>	Optional (for Windows only)
<b>Audio codec</b>	Realtek ALC663
<b>Audio features</b>	5.1 surround sound, High Definition audio, Internal speaker supports audio playback
<b>I/O CONTROLLER</b>	
<b>Serial ATA total</b>	6
<b>thereof eSATA</b>	1, optional
<b>SATA RAID support</b>	0, 1, 10, 5
<b>INTERFACES</b>	
<b>Audio: in (rear)</b>	2
<b>Audio: out (rear)</b>	1
<b>Front Audio: in</b>	1
<b>Front Audio: out</b>	1
<b>Internal speakers</b>	1
<b>USB 2.0 total</b>	13
<b>USB front</b>	2
<b>USB rear</b>	8
<b>USB internal</b>	2 + 1
<b>Display Port</b>	1 (depends on processor)
<b>VGA</b>	1 (depends on processor)
<b>DVI</b>	1 or 2, optional (depends on processor)
<b>Serial (RS-232)</b>	1, (9 pin)
<b>Mouse / Keyboard (PS/2)</b>	2
<b>Ethernet (RJ-45)</b>	1
<b>Parallel</b>	1, optional
<b>eSATA</b>	1, optional
<b>DRIVE BAYS</b>	
<b>Drive bays total</b>	8
<b>3.5-inch internal bays</b>	4
<b>3.5-inch external bays</b>	2
<b>5.25-inch external bays</b>	2
<b>SLOTS</b>	
<b>PCI-Express Gen2 x16</b>	1 x (312 mm) full height
<b>PCI-Express Gen2 x4 (mech. x16)</b>	1 x (190 mm) full height
<b>PCI-Express x1</b>	2 x (300 mm) full height
<b>PCI (32-bit / 33 MHz)</b>	3 x (312 mm)
<b>GRAPHICS ON BOARD</b>	
<b>Shared video memory</b>	up to 256 MB
<b>Refresh rate 1024 x 768 (recommended / max.)</b>	85 Hz /
<b>Refresh rate 1280 x 1024 (recommended / max.)</b>	85 Hz /
<b>Refresh rate 1600 x 1200 (recommended / max.)</b>	85 Hz /
<b>TFT resolution (VGA)</b>	1360 x 768 pixel 1440 x 900 pixel 1680 x 1050 pixel 1920 x 1200 pixel

---

## GRAPHICS ON BOARD

<b>TFT resolution (DVI)</b>	1360 x 768 pixel 1440 x 900 pixel 1680 x 1050 pixel 1920 x 1200 pixel
<b>Graphics notes</b>	Graphics controller integrated in dual-core processors. For quad-core processors graphics card is mandatory. Tested resolutions, depending on display type additional resolutions and frequencies possible Shared memory depending on main memory size For TFT we recommend using 60Hz

---

## ELECTRICAL VALUES

<b>Rated voltage range</b>	100 - 240 V
<b>Rated frequency range</b>	50 - 60 Hz
<b>Max. output of power supply</b>	300 W

---

## NOISE FOR STANDARD CONFIGURATION (HDD, ODD, FDD)

<b>Noise emission</b>	According to ISO9296 (LpAm at bystander position)
<b>Idle mode</b>	tbd
<b>Office mode</b>	tbd dB(A)
<b>Noise notes / description</b>	Actual noise emissions may vary depending on configuration

---

## DIMENSIONS / WEIGHT / ENVIRONMENTAL

<b>Dimensions (W x D x H)</b>	203 x 426 x 442 mm
<b>Operating position</b>	Vertical / horizontal
<b>Weight</b>	16 kg
<b>Weight notes</b>	Actual weight may vary depending on configuration
<b>Operating ambient temperature</b>	15 - 35°C
<b>Operating relative humidity</b>	10 - 75 %

---

## COMPLIANCE

<b>Product</b>	CELSIUS W380
<b>Model</b>	MTB-D2917
<b>Germany</b>	GS optional Blauer Engel / Blue Angel optional
<b>Europe</b>	CE
<b>USA/Canada</b>	FCC Class B cCSAus
<b>Global</b>	RoHS (Restriction of hazardous substances) Medical certification IEC60601-1-2 in combination with medical kit ENERGY STAR® 5.0
<b>Compliance notes</b>	Energy Star compliance may vary depending on actual configuration
<b>Compliance link</b>	<a href="https://sp.ts.fujitsu.com/sites/certificates/default.aspx">https://sp.ts.fujitsu.com/sites/certificates/default.aspx</a>

---

## SECURITY

<b>Physical security</b>	Kensington Lock support Eye for padlock Seal option Intrusion switch Optional: Integrated cabinet lock
<b>System security</b>	Write protect option for the Flash EPROM Embedded security (TPM 1.2) Disable / Hide TPM option
<b>User security</b>	Hard disk password User and supervisor BIOS password Optional: Access protection via SmartCard reader Optional: SmartCase Logon+

---

## OPERATING SYSTEM

<b>Operating system optional preinstalled</b>	Microsoft® Windows® 7 Professional 64-bit Microsoft® Windows® 7 Professional 32-bit Microsoft® Windows® 7 Home Premium 64-bit
---	---

---

---

**OPERATING SYSTEM**

**Operating system compatible** Microsoft® Windows Vista® Business 64-bit  
Microsoft® Windows Vista® Business 32-bit  
Microsoft® Windows® XP Professional x64 Edition  
Microsoft® Windows® XP Professional  
Linux

**Operating system notes** RedHat / Novell certification pending  
For some configurations third party drivers are currently not available or configuration restrictions may apply.

---

**ADDITIONAL SOFTWARE**

**Additional software (optional)** Drivers & Utilities DVD (DUDVD) Windows® 7 & Vista & XP  
Recovery DVD  
TwinLoad  
Windows® XP downgrade pack

**Additional software (included as a CD/DVD)** Norton Internet Security (incl. Firewall)

---

**MANAGEABILITY**

**Manageability features** iAMT Intel® Active Manageability Technology v6.0 (not activated, not set up)

**Manageability type** DeskView 10

**Manageability link** <http://ts.fujitsu.com/manageability>

---

**INPUT DEVICE / COMPONENTS**

**Input devices (optional)** Optical USB tilt wheel mouse  
Optical USB/PS2 tilt wheel mouse  
Space Explorer USB  
Space Navigator USB  
Space Pilot USB  
Keyboard

---

**Standard Warranty**

**Service Weblink** <http://ts.fujitsu.com/Supportservice>

#### FUJITSU PLATFORM SOLUTIONS

In addition to Fujitsu CELSIUS W380, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

#### Dynamic Infrastructures

With the Fujitsu Dynamic Infrastructures approach, Fujitsu offers a full portfolio of IT products, solutions and services, ranging from clients to datacenter solutions, Managed Infrastructure and Infrastructure-as-a-Service. How much you benefit from Fujitsu technologies and services depends on the level of cooperation you choose. This takes IT flexibility and efficiency to the next level.

#### Computing Products

[www.fujitsu.com/global/services/computing/](http://www.fujitsu.com/global/services/computing/)

#### Software

[www.fujitsu.com/software/](http://www.fujitsu.com/software/)

#### MORE INFORMATION

Learn more about Fujitsu CELSIUS W380, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website. <http://ts.fujitsu.com/celsius>

#### FUJITSU GREEN POLICY INNOVATION

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to resolve issues of environmental energy efficiency through IT.

Please find further information at <http://www.fujitsu.com/global/about/environment/>



#### COPYRIGHTS

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded.

Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see [http://ts.fujitsu.com/terms\\_of\\_use.html](http://ts.fujitsu.com/terms_of_use.html)

Copyright © Fujitsu Technology Solutions

#### DISCLAIMER

Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner

---

#### CONTACT

FUJITSU Technology Solutions

Website: <http://ts.fujitsu.com>

2010-01-05 CE-EN

---